



FEATURES



- 12 1" TFT LED Capacitive / Resistive Touch
- Intel Celeron Quad Core J1900 2.0GHz
- 1x DDR3L 1333MHz 4GB Max up to 8GB
- 2xLAN, 2xRS232/422/485, 8KV Static Electricity & 600W TVS Surge Protection
- Built in TPM2.0 for Hardware-based Security
- Wide voltage DC 9V~36V, with overcurrent, overvoltage and reverse connection protection
- 20°C ~ 70°C extended operating temperature
- IP66 Compliant Front Panel

SPECIFICATIONS

System		Touch screen	
CPU	Intel Celeron Quad Core J1900 2.0GHz	Touch Screen Type	Capacitive / Resistive Touch
L2 Cache	2MB	Transmittance	>90%
Chipsets	Intel Bay Trail SOC	Response Time	<5ms
Memory	DDR3L 1333MHz 4GB, Up to 8GB	Surface Hardness	≥7H
Harddisk	1 x mSATA 64G SSD / (128G / 240G / 480G SSD) optional	Supply Voltage	5.0V DC
Graphics	Intel HD Graphics	Touch Life	≥ 3000W
Network	Intel® I211-AT GbE LAN	Instituional	
Audio	Realtek ACL662 Audio controller	Material	High-strength Al-alloy, support IP66
TPM	TPM 2.0	Color	Gray
Operation System	Windows7 / 8 / 10, Linux, Unix, QNX	VESA Mounting	VESA: 100 x 100 mm
I / O		Waterproof Rate	IP65 / IP66
HDMI	1 x H-DMI	Product Dimension	314 x 216 x 60 mm
LAN	2 x LAN	Cut-out Size	300 x 203 mm
USB	3 x USB2.0 / 1 x USB3.0	Packing Size	450 x 170 x 350 mm
COM	2 x RS-232 / 422 / 485	Gross Weight	5 KG
Wireless Network	4G / WiFi / Bluetooth (Optional)	Power and Environment	
Other I/O Interface	1 x Power Switch	Operating Temperature	-20~70°C
LCD Panel		Storage Temperature	-20~80°C(-22~176°F)
Panel Size	12.1" Led	Relative Humidity	5%~95%@40°C, non-condensing
Resolution	1280 x 800	Vibration Range	5-500 Hz, 0.026 G2/Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Aspect Ratio	16:1		
Display Brightness	450 cd/m2	External Power Supply	AC 100 - 240V~50/60Hz, 1.5A
Contrast Ratio	700:1	Working Voltage	DC IN 9V~36V
Viewing Angle	80 / 80 / 80 / 60 (CR≥10) (L / R / U / D)	Power Consumption	≤30W



Dimension & I/O



I / O Definition:

- A. DC 9V-36V
- B. COM1:RS-232 / 422 / 485
- C. COM2:RS-232 / 422 / 485
- D. 2 x LAN
- E. H-DMI
- F. 1 x USB 3.0 / 1 x USB 2.0
- G. 2 x USB 2.0
- H. Audio
- I. Extension Switch
- J. Power Button

Panel Cutout Dimensions: 300 x 203 mm (11.81 x 8.00 in)

ORDERING INFORMATION

PACKING LIST

- 1x AS12.1-J1900-LC1 Series Industrial Panel PC
- 1x Utility DVD Driver
- 8x Embedded Buckles
- 1x Power Adaptor

AVAILABLE MODELS

Display Size	Resolution	Format	Brightness(cd/m ²)	Viewing Angle	LCD Color	Backlight MTBF
10.1"	1280 x 800	16:10	400 cd/m ²	85/85/85/85	262K/16.2M	30000 Hr (min.)
10.4"	800x600/1024x768	4:3	350 cd/m ²	80/80/65/75	262K/16.2M	30000 Hr (min.)
12.1"	800x600/1024x768	4:3	400 cd/m ²	80/80/65/75	262K/16.7M	30000 Hr (min.)
12.1"	1280x800	16:10	600 cd/m ²	88/88/88/88	262K/16.7M	50000 Hr (min.)
13.3"	1920x1080	16:9	400cd/m ²	85/85/85/85	262K/16.7M	50000 Hr (min.)
15"	1024x768	4:3	350cd/m ²	89/89/89/89	262K/16.2M	50000 Hr (min.)
15.6"	1920x1080	16:9	600cd/m ²	89/89/89/89	262K/16.2M	50000 Hr (min.)
17"	1280x1024	5:4	400cd/m ²	80/80/70/70	262K/16.7M	50000 Hr (min.)
17.3"	1920x1080	16:9	400cd/m ²	80/80/60/80	262K/16.7M	50000 Hr (min.)
19"	1280x1024	5:4	450cd/m ²	85/85/80/80	262K/16.7M	50000 Hr (min.)
21.5"	1920x1080	16:9	400d/m ²	89/89/89/89	262K/16.7M	50000 Hr (min.)
24"	1920x1080	16:9	350cd/m ²	89/89/89/89	262K/16.7M	50000 Hr (min.)

