



## FEATURES


- 15" TFT LED with Capacitive / Resistive Touch
- CPU: Intel Core 8th Gen i3 8145U / i5 8265U / i7 8565U (Optional)
- 1x DDR4L 2400MHz 4GB, Up to 64GB
- 2xLAN, 2xRS232/422/485, 8KV Static Electricity & 600W TVS Surge Protection
- Built-in TPM2 0 for Hardware based Security
- Wide voltage DC 9V~36V, Overcurrent, Overvoltage & Reverse Connection Protection
- 20°C ~ 70°C extended operating temperature
- IP66 Compliant Front Panel

## SPECIFICATIONS

System		Touch screen	
CPU	Intel Core i3-8145U / i5-8365U / i7-8565U	Touch Screen Type	Capacitive / Resistive Touch
L2 Cache	4MB / 6MB / 8MB	Transmittance	>90%
Memory	DDR4L 2400MHz 4GB, Up to 64GB	Response Time	<5ms
Harddisk	1 x M.2 120G SSD / (250G / 500G / 1TB SSD) Optional	Surface Hardness	≥7H
Graphics	intel HD Graphics 620	Supply Voltage	5.0V DC
Network	Intel® I211-AT GbE LAN	Touch Life	≥ 3000W
Audio	Realtek ACL662 Audio controller	Instituional	
TPM	TPM 2.0	Material	High-strength Al-alloy
Operation System	Windows 10 / 11 / Linux, Ubuntu, Debian	Color	Gray
I / O		VESA Mounting	VESA: 100 x 100 mm
HDMI	1 x H-DMI	Waterproof Rate	IP65 / IP66
LAN	2 x LAN	Product Dimension	361 x 285 x 62 mm
USB	3 x USB 3 0 / 1 x USB 2 0	Cut-out Size	347 x 271 mm
COM	2 x RS-232 / 422 / 485	Packing Size	460 x 180 x 400 mm
Audio	1x Audio_out & Mic_in	Gross Weight	7 KG
Wireless Network	WiFi / Bluetooth ( 4G / 5G Optional )	Power and Environment	
Other I/O Interface	1 x Power Switch	Operating Temperature	-20~70°C
LCD Panel		Storage Temperature	-30~80°C(-22~176°F)
Panel Size	15" LED	Relative Humidity	5%~95%@40°C, non-condensing
Resolution	1024 x 768	Vibration Range	5-500 Hz, 0.026 G2/Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Aspect Ratio	4:3		
Display Brightness	350 cd/m2	External Power Supply	AC 100 - 240V~50/60Hz, 1 5A
Backlight Lifetime	50000 Hr (min.)	Working Voltage	DC IN 9V~36V
Viewing Angle	89 / 89 / 89 / 89 (CR≥10) ( L / R / U / D )	Power Consumption	≤45W



## Dimension & I/O



Panel Cutout Dimensions: 347 x 271 mm (13.67 x 10.67 in )

## ORDERING INFORMATION

### PACKING LIST

- 1x AS15-I5-LC1
- 1x Utility DVD Driver
- 8x Embedded Buckles
- 1x Power Adaptor

## AVAILABLE MODELS

Display Size	Resolution	Format	Brightness(cd/m2)	Viewing Angle	LCD Color	Backlight MTBF
10.1"	1280 x 800	16:10	400 cd/m <sup>2</sup>	85/85/85/85	262K/16.2M	30000 Hr (min.)
10.4"	800x600/1024x768	4:3	350 cd/m <sup>2</sup>	80/80/65/75	262K/16.2M	30000 Hr (min.)
12.1"	800x600/1024x768	4:3	400 cd/m <sup>2</sup>	80/80/65/75	262K/16.7M	30000 Hr (min.)
12.1"	1280x800	16:10	600 cd/m <sup>2</sup>	88/88/88/88	262K/16.7M	50000 Hr (min.)
13.3"	1920x1080	16:9	400cd/m <sup>2</sup>	85/85/85/85	262K/16.7M	50000 Hr (min.)
15"	1024x768	4:3	350cd/m <sup>2</sup>	89/89/89/89	262K/16.2M	50000 Hr (min.)
15 6"	1920x1080	16:9	600cd/m <sup>2</sup>	89/89/89/89	262K/16 2M	50000 Hr (min )
17"	1280x1024	5:4	400cd/m <sup>2</sup>	80/80/70/70	262K/16 7M	50000 Hr (min )
17.3"	1920x1080	16:9	400cd/m <sup>2</sup>	80/80/60/80	262K/16 7M	50000 Hr (min )
19"	1280x1024	5:4	450cd/m <sup>2</sup>	85/85/80/80	262K/16 7M	50000 Hr (min )
21.5"	1920x1080	16:9	400d/m <sup>2</sup>	89/89/89/89	262K/16 7M	50000 Hr (min )
24"	1920x1080	16:9	350cd/m <sup>2</sup>	89/89/89/89	262K/16 7M	50000 Hr (min )

